



SC370 SIGNATURE CAPTURING DEVICE

Model	SC370
SPECIFICATIONS	
Dimensions (WxHxD)	154.5 × 120 × 9 mm
Weight	157g
Color	Black
Operating Condition	5 to 35 degrees C, Humidity:20 to 80%RH
Storage Condition	-20 to 60°C, Humidity:20% to 90%(no condensation)
Compatibility	USB 2.0
Cable	USB A or RS-232 cable
Power Management	USB BUS power (5V, 100mA)
Power Consumption	With USB BUS Power: under 0.5 W
DISPLAY	
Display Panel	Monochrome LCD 240×120
Display Area	76.78 × 39.58mm
Resolution	240 × 120
Active Area	76.78 × 39.58 mm
Pixel pitch	0.32 × 0.33 mm
Pixel size	0.3 × 0.31 mm
Viewing Angles	(horizontal/vertical)70/70deg
Contrast Ratio	3.1 (typ.)
(Display: White/Black)	
Display Response(Tr + Tf)	307 ms (typ.) : White → Black : 202 ms (typ.) Black → White : 105 ms (typ.)
TABLET	
Technology	Electro-magnetic resonance technology
Active Area	76.78 × 39.58 mm
Resolution	0.01mm/dot 2540lpi
Coordinate Accuracy	± 0.5 mm
Accuracy Assurance Height	7 mm or more
Maximum Pen Tilt Range	Up to 50°from vertical
Pressure Sensitivity	512 levels
Report Rate(max)	150pps
PEN	
Pressure Sensitivity	512 levels
Dimensions	9(Φ)×131.2 (length)mm
Weight	8.48g

